



(19)

(11) Publication number: **2001205055**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **2000022196**

(51) Intl. Cl.: **B01D 65/02 B01D 63/08 C02F 1/00 C02F 1/44**

(22) Application date: **31.01.00**

(30) Priority:

(43) Date of application
publication: **31.07.01**

(84) Designated contracting
states:

(71) Applicant: **DAICEL CHEM IND LTD**

(72) Inventor: **HAMADA TOYOZO
NAKATSUKA NOBUYUKI**

(74) Representative:

(54) METHOD FOR OPERATING MEMBRANE SEPARATION APPARATUS AND APPARATUS THEREFOR

(57) Abstract:

PROBLEM TO BE SOLVED: To obtain method for operating a membrane separation apparatus which enables energy saving filtration operation, can simply clean a filter medium by removing sludge after the solid-liquid separation of bio-treated wastewater containing activated sludge, etc., can maintain a large amount of filtrate over a long period, and is high in efficiency and a device for the method.

SOLUTION: The membrane separation apparatus housing bag-shaped plane membrane elements in which a nonwoven fabric 10-1,000 g/m² in base weight and 0.1-200 cm³/cm².s in gas permeability is used as the filter medium is installed separately from a bio-reactor for treating activated sludge, a pump is placed between the bio-reactor and the membrane separation apparatus, gas is introduced into piping on the downstream side of the pump, and a

bio-treatment liquid from the bio-reactor is supplied as a gas-liquid mixed flow between the membrane elements installed in the membrane separation apparatus and filtered. After the filtration, by supplying a cleaning fluid from the permeation side of the filter medium to the raw liquid side, fluid back-washing and/or washing by the bio-treatment liquid for cleaning the surface or inside of the filter medium or membrane surface flash cleaning by a gas-liquid mixed flow in which gas is mixed with the bio-treatment liquid are repeated intermittently.

COPYRIGHT: (C)2001,JPO